



ASPHALT FINISHER

MODEL : PAF600

TECHNICAL SPECIFICATIONS

POWERPAC
POWERPLUS GROUP INC. USA

■ MAIN SPECIFICATIONS

Minimum width of paving: (mm) 2500
Maximum width of paving: (mm) 6000
Minimum thickness of paving: (mm) 10
Maximum thickness of paving: (mm) 250
Paving speed: (m/min) 2.03~6.07
Traveling speed: (km/h) 1.55~4.62
Hopper capacity: (t) 10
Maximum theoretical output: (t/h) 400
Length: (mm) 5740
Width: (mm) 4534
Height: (mm) 2995
System voltage: (V) 24, DC

■ ENGINE

Model: Deutz F4L912 (Tech.)
Type: Air cooled with 4 cylinders
Rated Output: (HP) 63 / 2000 rpm
Fuel tank capacity: (L) 118

■ WORKING DEVICES

Mechanical extension screed

1. Screed plate
Basic width: (mm) 2500
Crown adjustment: (%) 4
2. Vibrating frequency: (Hz) 0~50
3. Extension screed: (mm) 0.75 -2 sections

■ TRAVELLING DEVICES

1. Mechanical clutch and transmission gear box
2. Undercarriage: Track Type

■ AUTOMATIC LEVELING DEVICES

1. Two automatic slope devices
2. One automatic grade leveling device

