



ASPHALT FINISHER

MODEL : PAF600W

TECHNICAL SPECIFICATIONS

POWERPAC
POWERPLUS GROUP INC. USA

■ MAIN SPECIFICATIONS

Minimum width of paving: (mm) 2800
Maximum width of paving: (mm) 6000
Minimum thickness of paving: (mm) 10
Maximum thickness of paving:(mm) 250
Paving speed: (m/min) 3.07~9.16
Traveling speed: (km/h) 2.30~16.84
Hopper capacity: (t) 12
Maximum theoretical output: (t/h) 300
Length: (mm) 6394 (6064mm when transportation)
Width: (mm) 3000 (2733mm when transportation)
Height: (mm) 3695 (2888mm when transportation)
System voltage: (V) 24,DC

■ ENGINE

Model: Deutz F6L913T (Tech.)
Type: Air cooled with 6 cylinders
Rated Output: (HP) 118 / 2300 rpm
Fuel tank capacity: (L) 200

■ WORKING DEVICES

Mechanical extension screed

1. Screed
Basic width: (mm) 2800
Crown adjustment: (%) 4
2. Vibrating frequency: (Hz) 0~50

■ TRAVELLING DEVICES

1. Mechanical clutch and transmission gear box
2. Final drive: Differential mechanism with semi axle
3. Undercarriage: Wheel Type

■ AUTOMATIC LEVELING DEVICES

1. Two automatic slope leveling devices
2. One automatic grade leveling device

