



# ASPHALT FINISHER

MODEL : PAF700

## TECHNICAL SPECIFICATIONS

**POWERPAC**  
POWERPLUS GROUP INC., USA

### ■ MAIN SPECIFICATIONS

Minimum width of paving: (mm) 3000  
Maximum width of paving: (mm) 7000  
Minimum thickness of paving: (mm) 20  
Maximum thickness of paving: (mm) 300  
Paving Speed: (m/min) 2.00~3.60  
Traveling Speed: (km/h) 0.90~2.86  
Hopper Capacity: (t ) 12  
Maximum theoretical output: (t/h) 400  
Length: (mm) 6565  
Width: (mm) 3210  
Height: (mm) 3050  
System voltage: (V) 24, DC

### ■ ENGINE

Model: Deutz BF6L913T (Tech.)  
Type: Air cooled with six cylinders  
Rated Output: (HP) 118 / 2300 rpm  
Fuel Tank capacity: (L) 190

### ■ WORKING DEVICES

Mechanical extension screed

1. Screed  
Basic width: (mm) 3000  
Crown adjustment: (%) 0-4
2. Vibrating frequency: (Hz) 0-50

### ■ TRAVELLING DEVICES

1. Mechanical clutch and transmission gear box
2. Undercarriage: Track Type

### ■ AUTOMATIC LEVELING DEVICES

1. Two grade leveling devices
2. One slope leveling device

