



ASPHALT FINISHER

MODEL : PAF900

TECHNICAL SPECIFICATIONS

POWERPAC
POWERPLUS GROUP INC., USA

■ MAIN SPECIFICATIONS

Minimum width of paving: (mm) 3000
Maximum width of paving: (mm) 9000
Minimum thickness of paving: (mm) 20
Maximum thickness of paving: (mm) 320
Paving Speed: (m/min) 2.00~6.25
Traveling Speed: (km/h) 0.96~2.86
Hopper Capacity: (t) 12
Maximum theoretical output: (t/h) 500
Weight: (kg) 16000~20500
Length: (mm) 6220
Width: (mm) 3270
Height: (mm) 3050



■ ENGINE

Model: Deutz BF6L913 (Tech.)
Type: Air cooled with six cylinders
Rated Output: (HP) 152 / 2300 rpm

■ WORKING DEVICES

Mechanical extension screed with tamper

1. Tamper : Single, fixed amplitude

Stroke: (mm) 5

Pressure: (Mpa) 14

2. Extended screeds

1.25m 2 segments

1m 2 segments

0.5m 2 segments

0.25m 2 segments

■ TRAVELLING DEVICES

1. Mechanical clutch and transmission gear box

2. Undercarriage: Track Type

■ AUTOMATIC LEVELING DEVICES

1. Two grade leveling device

2. One slope leveling device